Cable assemblies

Industrial three pin cable assemblies

Model number	Description	Compatible accelerometers
	Twist lock cables	
	for the second	
CMSS 933-68TLN-SY-5M	Twist lock, non-isolated Two wire, IP 68 connector, twist lock, non-isolated, single shield,	
CMSS 933-68TLN-SY-10M	yellow cable, 5 m (16.4 ft.) length Two wire, IP 68 connector, twist lock, non-isolated, single shield,	
CMSS 933-68TLN-SY-10M	yellow cable, 10 m (32.8 ft.) length Two wire, IP 68 connector, twist lock, non-isolated, single shield, yellow cable, 20 m (65.6 ft.) length	
	Twist lock, isolated	
CMSS 933-68TLI-SY-5M	Two wire, IP 68 connector, twist lock, isolated, single shield, yellow cable, 5 m (16.4 ft.) length	
CMSS 933-68TLI-SY-10M	Two wire, IP 68 connector, twist lock, isolated, single shield, yellow cable, 10 m (32.8 ft.) length	
CMSS 933-68TLI-SY-10M	Two wire, IP 68 connector, twist lock, isolated, single shield, yellow cable, 20 m (65.6 ft.) length	• CMSS 786T-IS • CMSS 793T-3
	Locking collar cables	CMSS 797T-1CMSS 2100TCMSS 2200T
CMSS 933-68LCN-SY-5M	Locking collar, non-isolated Two wire, IP 68 connector, locking collar, non-isolated, single	
CMSS 933-68LCN-SY-10M	shield, yellow cable, 5 m (16.4 ft.) length Two wire, IP 68 connector, locking collar, non-isolated, single	
CMSS 933-68LCN-SY-10M	shield, yellow cable, 10 m (32.8 ft.) length Two wire, IP 68 connector, locking collar, non-isolated, single	
	shield, yellow cable, 20 m (65.6 ft.) length	
CMSS 933-68LCI-SY-5M	Locking collar, isolated Two wire, IP 68 connector, locking collar, isolated, single shield,	
CMSS 933-68LCI-SY-10M	yellow cable, 5 m (16.4 ft.) length Two wire, IP 68 connector, locking collar, isolated, single shield,	
CMSS 933-68LCI-SY-10M	yellow cable, 10 m (32.8 ft.) length Two wire, IP 68 connector, locking collar, isolated, single shield,	
CINDS 733-00[CI-31-10M	yellow cable, 20 m (65.6 f t.) length	
	Longer cable lengths are available upon request. Please	
	contact your SKF Sales Representative.	