

技术咨询与报价

电话: 18823303057 QQ:2104028976

Standard Size (5 3/4") **With Conductive Silicone Cups**
Temperature Range (-65°F to 445°F) (-55°C to 230°C)

SELF CONTAINED PEN-VAC® & VACULA 3 ESD-SAFE Vacuum Handling Tools

PEN-VAC® Kit With 4 Probes + Cups

PEN-VAC® with three bent probes with 1/8" (3.18mm), 1/4" (6.35mm), 3/8" (9.53mm), diameter vacuum cups, one straight probe with 1/4" (6.35mm) diameter vacuum cup.

V8901-A-ESD Standard PEN-VAC®, With Conductive Silicone Cups



PEN-VAC® Kit With 6 Probes + Cups

PEN-VAC® with two of each size cup on one bent and one straight probe. Cup sizes are 1/8" (3.18mm), 1/4" (6.35mm), 3/8" (9.53mm) diameter.

V8901-LMS-ESD Standard PEN-VAC®, With Conductive Silicone Cups



PEN-VAC® With 6 Probes + Cups

PEN-VAC® with two of each size cup on one bent and one straight probe. Cup sizes are 1/4" (6.35mm), 3/8" (9.53mm), 1/2" (12.7mm) diameter.

V8901-HLM-ESD Standard PEN-VAC®, With Conductive Silicone Cups



PEN-VAC® Kit With 10 Probes + Cups

PEN-VAC® with two of each size cup on one bent and one straight probe. Cup sizes are 1/8" (3.18mm), 3/16" (4.76mm), 1/4" (6.35mm), 3/8" (9.53mm), 1/2" (12.7mm) diameter.

V8901-TEN-ESD Standard PEN-VAC®, With Conductive Silicone Cups



PEN-VAC® Without Probes or Vacuum Cups

PEN-VAC® only. You order the probes and cups that you need. See pages 8 and 9 for details.

V8901-X-ESD Standard PEN-VAC®

No Probes or Cups.

VACULA 3 Kit With 3 Cups

Our most powerful ESD-safe self contained tweezer designed to handle parts when moving them into and out of burn-in trays, test sockets or other component transfer operations. The plunger in the rear of the tool activates the vacuum. The VC-3 is provided without or with three vacuum cups, 1/2" (12.7mm), 5/8" (15.88mm) and 3/4" (19.05) diameter, that slip onto a dual barbed fitting. The barbed fitting provides extra lifting power.

VC-3-B With 3 Cups -Dual Barbed Fitting/Luer Slip Tip - With a 1/2" (12.7mm), 5/8" (15.88mm) and 3/4" (19.05mm) diameter Static Dissipative Buna-N Cups

VC-3-ESD With 3 Cups -Dual Barbed Fitting/Luer Slip Tip - With a 1/2" (12.7mm), 5/8" (15.88mm) and 3/4" (19.05mm) diameter Conductive Silicone Cups

VC-3-X Tool Only, No Cups or Probes



VACULA 3 Kit With Barbed Anti-Wobble Fitting And 1 Cup

Our most powerful ESD-safe self contained tweezer designed to handle parts when moving them into and out of burn-in trays, test sockets or other component transfer operations. The plunger in the rear of the tool activates the vacuum. The VC-3-AW is provided with one vacuum cup 3/4" (19.05) diameter, that slip onto a barbed anti-wobble fitting. The barbed fitting provides extra lifting power.

VC-3-075-AW-B With barbed anti-wobble fitting & 3/4" (19.05mm) diameter Static Dissipative Buna-N Cup

VC-3-075-AW-ESD With barbed anti-wobble fitting & 3/4" (19.05mm) diameter Conductive Silicone Cup



Our PEN-VAC® line offers a replacement for SMD tweezers. The soft suction cup material will not scratch your parts or damage delicate leads. This is an excellent tool for pick-and-place of many standard and odd size SMT components.

STANDARD SIZE
5" (139.7mm) long
3/8" (9.53mm) diameter

Vacuum push plunger

Black aluminum body

Dual barbed cup retainer

Quick change vacuum cup

